



**AUH 630 / AUH 800**  
Flyer Overhead Pay-off

# AUH 630 / AUH 800

## Design:

- With horizontal spool axis
- dancer-controlled strap brake for prevention of flyer stop-delay (in the event of an emergency stop or wire break)
- cassette frames for 1, 2 and 4 pay-off positions

## Increase in quality:

- bundle pay-off with weight-loaded dancer for constant wire tension (incl. run-up and return)

## Increase in productivity:

- quick spool-change device with 2 spool mounting mandrels on one pivoting column

## Options:

- handling systems for spool loading

## Technical data

type		AUH 630	AUH 800
max. pay-off speed	m/min	300	300
	fpm	985	985
single wire dia. (Cu soft)	mm	0.10 ... 0.50	0.10 ... 0.50
	AWG	38 ... 24	38 ... 24
wire bundle cross-section (Cu soft)	mm <sup>2</sup>	0.25 ... 1.57	0.25 ... 1.57
	AWG	23 ... 15	23 ... 15
spool dimensions			
	max. flange dia.	mm 630	800
	min. barrel dia.	mm 315	400
	min. bore dia.	mm 100	125
machine dimensions (W x D x H) (with 3 pay-off positions)		m 1.60 x 3.40 x 1.12	1.12 x 6.90 x 1.32
weight		kg approx. 1,350	approx. 2,100